


BSE **O**BSTRUCTION LIGHTS

Compliances: FAA AC 150/5345-43: L-810 FCC Rules and Regulations Canadian Standards Association (CSA) ICAO ANNEX 14

OB.LIGHT LED SOLARCELL Model : 1296W5ABL





Applications :

The 1269W5ABL is the world's most advance solar-powered LED obstruction light with 2 miles of visibility. Installation for permanent or temporary obstruction lighting applications, Cranes, Wind energy masts, Telecommunication towers, Remote weather stations, Buildings, Barricade lighting, Airports

Specifications :

Specifications.	
Light output Flashing	5 step ; Change flash pattern by tact switch
Light source	5,000 mcd. LEDs ;Red With LED Reflector. International patents pending.
Solar Module	5 watt
Battery	<u>></u> 5 ah at 12 V ;Seal lead acid
Peak Intensity	> 15 cd. ; 2 mile range
Vertical Divergence	+/- 8 degrees
Autonomy-Darkness	10-15 days typical ; 10% duty cycle, 12 hour night
Storage	On/Off Switch ; Turn on in the day when illuminant about 31.5 Lux. And turn off
	at dawn
Environmental	Ambient temperature range -30°C to +85°C
Protection	IP 65
Weight	5.5 kg
Lens	White fresnel glass globes for 360O visibility
Body	Cast aluminum housing with yellow finish ,O-Ring globe seal
Warranty	5 years LED Lamps & Solar cell, only 1 year Battery
Operating test function	By press and hold switch "Set" and open switch on and release witch "Set"
	Obstrucle will operating in suddenly. Cancel function by press switch off and
	re-operating test function test again.
Protection Battery function	There are prevents battery decline system ; If the battery voltage is reduced to
	approximately 10.3 Vdc these system will control the lamp stops to working And can
	start again when a new charge to the battery up to 11.7 Vdc.
Alarm System	Lamp Alarm : Will show when the lamp was failed and Battery Alarm : when battery
	voltage is reduced to approximately 8.12 Vdc and alarm will able to clear yourself if
	battery is re-charge voltage up to approximately 9.2 Vdc.

Installation :

Completely integrated, self - contained, waterproof and compact, Installs in minutes using two screw or bolts, No external wiring



B.S.E. ELECTRONIC CO., LTD. (THAILAND)

Tel. (662)803-6303-4, (662)803-7637 Fax. (662)803-7636

Website : www.bseelectronic.com E-Mail : info@bseelectronic.com