

BSE OBSTRUCTION LIGHTS

Compliances: FAA AC 150/5345-43: L-810 FCC Rules and Regulations Canadian Standards Association (CSA) ICAO ANNEX 14

LED Obstruction light Single Assembly Made in THAILAND

Model: 48W5



Compliance with following Specification AC # 1505345-43E ICAO (ANNEX 14,THIRD EDITION-JULY 1999 Chapter 6)

Obstruction light is the first certified LED based L-810 obstruction light. Designed for steady burning. This fixture Is used to mark any obstacle that may present hazards to aircraft navigation



Features

- LED Red lamp , Chip technology –AllnGap / Gap and Standard 5 mm (T-1 ¾") Water clear package
- More than 70,000 Hours life average at normal usage.
- Low power consumption 5 W (+1 W) at DC 48 V.
- Transient protection circuit over to 6KV 3 KA standard
- Properties structure to be Earth grounding provisions provided
- Unique optically designed lens to enhance LED operation and provide 360°visibility at 15 cd typical
- Weather/corrosion resistant lamp assembly and housing IP 65
- Self-contained winding compartment eliminates additional boxes
- Single fixture
- Threaded ¾" bottom hub for mounting
- * Obstruction light LED 48VDC double type Model: 48W5D

Weight: SINGLE OB.LIGHT 4.5 lbs, 2.0 kg

B.S.E. ELECTRONIC CO., LTD. (THAILAND) Tel. (662)803-6303-4, (662)803-7637 Fax. (662)803-7636 Website : www.bseelectronic.com E-Mail :info@bseelectronic.com

BSE